

# Conversion Guide for 3M™ Secure Click™ Half Facepiece Reusable Respirator HF-800 Series

Designed with smart and intuitive features, the 3M Secure Click Half Facepiece Reusable Respirator helps protect workers from particulates and/or a wide variety of gases and vapors when used with approved 3M Secure Click filters and cartridges shown below.

If you are currently using a 3M respirator with a bayonet connection, this guide will offer conversion suggestions to help you transition to 3M Secure Click.



**Please note:** This list shows our current offering of 3M Secure Click filters and cartridges. If your filter or cartridge is not shown here, no equivalent exists as of November, 2019.

	Gas and Vapor Cartridges	Combination Cartridges
3M Bayonet Connection	 6001 OV  6003 OV/AG  6006 MG/V	 60921 OV/P100  60923 OV/AG/P100  60926 MG/V/P100
3M™ Secure Click™ Connection	 D8001 OV  D8003 OV/AG  D8006 MG/V	 D80921 OV/P100  D80923 OV/AG/P100  D80926 MG/V/P100

	P95 Particulate Filters	P100 Particulate Filters
3M Bayonet Connection	 2071  2076HF*  2078**	 2091  2096*  2097***
3M™ Secure Click™ Connection	 D3071  D3076HF*  D3078**	 D3091  D3096*  D3097***

\* 3M-recommended for relief against nuisance levels of acid gases.  
 \*\* 3M-recommended for relief against nuisance levels of organic vapor/acid gases.  
 \*\*\* 3M-recommended for relief against nuisance levels of organic vapors.  
 Nuisance level refers to concentrations not exceeding the OSHA PEL or applicable government occupational exposure limits, whichever is lower

	Replaceable Particulate Filters	Replaceable Filter Retainer
3M Bayonet Connection	 5N11 N95  5P71 P95	 501 Filter Retainer
3M™ Secure Click™ Connection	 D7N11 N95  D7P71 P95	 D701 Filter Retainer

**⚠WARNING**

These respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For correct use, see supervisor and User Instructions, or call 3M PSD Technical Service in USA at 1-800-243-4630 and in Canada at 1-800-267-4414.